

62000 Propeller Shaft Grease

Document version: 1 aug. 2020



Description

This propeller shaft grease is specially developed for applications on board ships. The grease has a very high resistance to water washout and is therefore particularly suitable for use in stern tubes. This grease is suitable for lubricating rudder and rudder stock, capstans, anchor winches, winches and in case of humid environment.

According to the specifications of

Packaging units

DIN 51502 ISO 673 / L-XBC IB2 KP2K-20

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
62000	0.4 kg	12	-
62001	1 kg	6	-
62005	5 kg	1	-
62018	18 kg	1	-
62050	50 kg	1	-
62185	185 kg	1	-

MPM International Oil Company B.V. Cyclotronweg 1 2629 HN Delft Fax number: +31 (0)15 - 251 40 31 info@mpmoil.nl www.mpmoil.nl TEST

Soap

TEST	VALUE	
NLGI Classification	2	
Base Oil	Mineral	
Colour	Brown	
Kinematic Viscosity at 40°C	100	mm2/s
Temperature Range	-10 / 90	°C
Water Resistance	Insoluble	
Soap Thickener	Lithium-Calcium	

These characteristics are typical of current production. Variations in these characteristics may occur.

Page 2/2

MPM International Oil Company B.V. Cyclotronweg 1 2629 HN Delt Fax number: +31 (0)15 - 251 40 31 info@mpmoil.nl www.mpmoil.nl 2629 HN Delft