



DRIVING SURFACE PERFECTION

RAPTOR EPOXY PRIMER HARDENER

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
 SDS Ref. (EU): REPH
 Date of issue: 12/01/2017 Revision date: 28/11/2018 Supersedes: 12/01/2017 Version: 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Trade name : RAPTOR EPOXY PRIMER HARDENER
 Product code : REP/1LK, REP/5LK, RC/EP5LK
 Product group : Epoxy hardener

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : For professional use only
 Industrial
 Function or use category : Hardener (Crosslinker)

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

U-POL LIMITED
 Denington Road, Wellingborough
 Northants. NN8 2QH - UK
 T +44 (0) 1933 230310
technical.department@u-pol.com - www.u-pol.com

1.4. Emergency telephone number

Emergency number : CHEMTREC - +44 (0) 870 8200418 (24 hrs)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals-24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	NHS England, Scotland & Wales	-	Call 111 or a Doctor	In Northern Ireland, contact your local GP or pharmacist during normal hours (www.gpoutofhours.hscni.net)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226
 Acute toxicity (oral), Category 4 H302
 Acute toxicity (inhalation:dust,mist) Category 4 H332
 Skin corrosion/irritation, Category 1B H314
 Serious eye damage/eye irritation, Category 1 H318
 Skin sensitisation, Category 1 H317
 Specific target organ toxicity — Single exposure, Category 3, Narcosis H336
 Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation H335
 Specific target organ toxicity — Repeated exposure, Category 2 H373
 Full text of H statements : see section 16


Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour. May cause damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness. Harmful if inhaled. Harmful if swallowed. May cause respiratory irritation. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



RAPTOR EPOXY PRIMER HARDENER

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Signal word (CLP)	: Danger
Hazardous ingredients	: xylene; m-phenylenebis(methylamine); 1-methoxy-2-propanol; benzyl alcohol
Hazard statements (CLP)	: H226 - Flammable liquid and vapour. H302+H332 - Harmful if swallowed or if inhaled. H314 - Causes severe skin burns and eye damage. H317 - May cause an allergic skin reaction. H335 - May cause respiratory irritation. H336 - May cause drowsiness or dizziness. H373 - May cause damage to organs through prolonged or repeated exposure.
Precautionary statements (CLP)	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260 - Do not breathe fume, vapours, spray. P280 - Wear face protection, protective clothing, protective gloves. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P305 - IF IN EYES: Rinse first with plenty of water and if necessary take medical advice. P312 - Call a doctor if you feel unwell.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
1-methoxy-2-propanol	(CAS-No.) 107-98-2 (EC-No.) 203-539-1 (EC Index-No.) 603-064-00-3	25 - 50	Flam. Liq. 3, H226 STOT SE 3, H336
xylene	(CAS-No.) 1330-20-7 (EC-No.) 215-535-7 (EC Index-No.) 601-022-00-9	25 - 50	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315
benzyl alcohol	(CAS-No.) 100-51-6 (EC-No.) 202-859-9 (EC Index-No.) 603-057-00-5	5 - 10	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332
m-phenylenebis(methylamine)	(CAS-No.) 1477-55-0 (EC-No.) 216-032-5	5 - 10	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

RAPTOR EPOXY PRIMER HARDENER

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe vapours, fume, spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe vapours, spray, fume. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

xylene (1330-20-7)

EU	Local name	Xylene, mixed isomers, pure
EU	IOELV TWA (mg/m ³)	221 mg/m ³
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m ³)	442 mg/m ³
EU	IOELV STEL (ppm)	100 ppm
EU	Notes	Skin
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Ireland	Local name	Xylene, mixed isomers
Ireland	OEL (8 hours ref) (mg/m ³)	221 mg/m ³
Ireland	OEL (8 hours ref) (ppm)	50 ppm
Ireland	OEL (15 min ref) (mg/m ³)	442 mg/m ³

RAPTOR EPOXY PRIMER HARDENER

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

xylene (1330-20-7)		
Ireland	OEL (15 min ref) (ppm)	100 ppm
Ireland	Notes (IE)	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
Ireland	Regulatory reference	Code of Practice for the Chemical Agents Regulations 2018
United Kingdom	Local name	Xylene
United Kingdom	WEL TWA (mg/m ³)	220 mg/m ³
United Kingdom	WEL TWA (ppm)	50 ppm
United Kingdom	WEL STEL (mg/m ³)	441 mg/m ³
United Kingdom	WEL STEL (ppm)	100 ppm
United Kingdom	Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
United Kingdom	Regulatory reference	EH40/2005 (Third edition, 2018). HSE

m-phenylenebis(methylamine) (1477-55-0)		
Ireland	Local name	m-Xylene α,α' -diamine (m-phenylenebis(methylamine))
Ireland	OEL (8 hours ref) (mg/m ³)	0.1 mg/m ³
Ireland	Regulatory reference	Code of Practice for the Chemical Agents Regulations 2018

1-methoxy-2-propanol (107-98-2)		
EU	Local name	1-Methoxypropanol-2
EU	IOELV TWA (mg/m ³)	375 mg/m ³
EU	IOELV TWA (ppm)	100 ppm
EU	IOELV STEL (mg/m ³)	568 mg/m ³
EU	IOELV STEL (ppm)	150 ppm
EU	Notes	Skin
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Ireland	Local name	Propylene glycol monomethyl ether
Ireland	OEL (8 hours ref) (mg/m ³)	375 mg/m ³
Ireland	OEL (8 hours ref) (ppm)	100 ppm
Ireland	OEL (15 min ref) (mg/m ³)	568 mg/m ³
Ireland	OEL (15 min ref) (ppm)	150 ppm
Ireland	Notes (IE)	IOELV (Indicative Occupational Exposure Limit Values)
Ireland	Regulatory reference	Code of Practice for the Chemical Agents Regulations 2018
United Kingdom	Local name	1-Methoxypropan-2-ol
United Kingdom	WEL TWA (mg/m ³)	375 mg/m ³
United Kingdom	WEL TWA (ppm)	100 ppm
United Kingdom	WEL STEL (mg/m ³)	560 mg/m ³
United Kingdom	WEL STEL (ppm)	150 ppm
United Kingdom	Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
United Kingdom	Regulatory reference	EH40/2005 (Third edition, 2018). HSE

RAPTOR EPOXY PRIMER HARDENER

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: amber.
Odour	: Amine-like.
Odour threshold	: No data available
pH	: No data available
pH solution	: > 7.5
Relative evaporation rate (butylacetate=1)	: ≈ 13
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 24 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: 0.93 kPa
Relative vapour density at 20 °C	: No data available
Relative density	: 0.96
Solubility	: Immiscible with water.
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: ≈
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content : 651 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour.

10.2. Chemical stability

Stable at ambient temperature and under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Acids. Oxidising agents. Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Hazardous decomposition products may be released during prolonged heating like smokes, carbon monoxide and dioxide.

RAPTOR EPOXY PRIMER HARDENER

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Oral: Harmful if swallowed.
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Inhalation:dust,mist: Harmful if inhaled.

ATE CLP (oral)	1194.886 mg/kg
ATE CLP (dermal)	2750.12 mg/kg
ATE CLP (vapours)	69.07 mg/l
ATE CLP (dust,mist)	15.7 mg/l

benzyl alcohol (100-51-6)

LD50 oral rat	1620 mg/kg bw/day (Rat, Male, Experimental value, Oral)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit, Inconclusive, insufficient data, Dermal)
LC50 inhalation rat (mg/l)	> 4.178 mg/l air (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male/female, Experimental value, Inhalation (aerosol))

xylene (1330-20-7)

LD50 oral rat	3523 mg/kg bodyweight (Equivalent or similar to EU Method B.1: Acute Toxicity (Oral), Rat, Male, Experimental value, Oral, 14 day(s))
---------------	---

1-methoxy-2-propanol (107-98-2)

LD50 oral rat	4016 mg/kg bodyweight (EU Method B.1 tris: Acute oral toxic – Acute toxic class method, Rat, Male/female, Experimental value, Oral)
LD50 dermal rat	> 2000 mg/kg bodyweight (Other, 24 h, Rat, Male/female, Experimental value, Dermal)

Skin corrosion/irritation : Causes severe skin burns and eye damage.
Serious eye damage/irritation : Causes serious eye damage.
Respiratory or skin sensitisation : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

xylene (1330-20-7)

IARC group	3 - Not classifiable
------------	----------------------

Reproductive toxicity : Not classified
STOT-single exposure : May cause drowsiness or dizziness. May cause respiratory irritation.
STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. Before neutralisation, the product may represent a danger to aquatic organisms.
Acute aquatic toxicity : Not classified
Chronic aquatic toxicity : Not classified

benzyl alcohol (100-51-6)

LC50 fish 1	460 mg/l (EPA OPP 72-1, 96 h, Pimephales promelas, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 Daphnia 1	230 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Fresh water, Experimental value, GLP)
ErC50 (algae)	770 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

RAPTOR EPOXY PRIMER HARDENER

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

xylene (1330-20-7)	
LC50 fish 1	2.6 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static renewal, Fresh water, Read-across, Lethal)
ErC50 (algae)	4.36 mg/l (OECD 201: Alga, Growth Inhibition Test, 73 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

1-methoxy-2-propanol (107-98-2)	
LC50 fish 1	>= 1000 mg/l (Equivalent or similar to OECD 203, 96 h, Oncorhynchus mykiss, Semi-static system, Fresh water, Experimental value, Nominal concentration)
ErC50 (algae)	> 1000 mg/l (Other, 168 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

12.2. Persistence and degradability

benzyl alcohol (100-51-6)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.6 g O ₂ /g substance
Chemical oxygen demand (COD)	2.4 g O ₂ /g substance
ThOD	2.5 g O ₂ /g substance

xylene (1330-20-7)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.

1-methoxy-2-propanol (107-98-2)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
ThOD	1.95 g O ₂ /g substance

12.3. Bioaccumulative potential

benzyl alcohol (100-51-6)	
Log Pow	1 - 1.1 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

xylene (1330-20-7)	
BCF fish 1	7.2 - 25.9 (56 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Read-across)
Log Pow	3.2 (Read-across, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

1-methoxy-2-propanol (107-98-2)	
BCF fish 1	1 (Pimephales promelas)
Log Pow	< 1 (Experimental value, Equivalent or similar to OECD 117, 20 °C)
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

benzyl alcohol (100-51-6)	
Surface tension	39 mN/m (20 °C)
Ecology - soil	No (test)data on mobility of the substance available.

xylene (1330-20-7)	
Surface tension	28.01 - 29.76 mN/m (25 °C)
Log Koc	2.73 (log Koc, Equivalent or similar to OECD 121, Read-across)
Ecology - soil	Low potential for adsorption in soil. May be harmful to plant growth, blooming and fruit formation.

RAPTOR EPOXY PRIMER HARDENER

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

1-methoxy-2-propanol (107-98-2)

Surface tension	0.0707 N/m (20 °C, 1 g/l, OECD 115: Surface Tension of Aqueous Solutions)
Ecology - soil	Low potential for adsorption in soil.

12.5. Results of PBT and vPvB assessment

Component

xylene (1330-20-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
1-methoxy-2-propanol (107-98-2)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
benzyl alcohol (100-51-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
3470	3470	3470	3470	3470
14.2. UN proper shipping name				
PAINT, CORROSIVE, FLAMMABLE	PAINT, CORROSIVE, FLAMMABLE	Paint, corrosive, flammable	PAINT, CORROSIVE, FLAMMABLE	PAINT, CORROSIVE, FLAMMABLE
Transport document description				
UN 3470 PAINT, CORROSIVE, FLAMMABLE, 8 (3), II, (D/E)	UN 3470 PAINT, CORROSIVE, FLAMMABLE, 8 (3), II	UN 3470 Paint, corrosive, flammable, 8 (3), II	UN 3470 PAINT, CORROSIVE, FLAMMABLE, 8 (3), II	UN 3470 PAINT, CORROSIVE, FLAMMABLE, 8 (3), II
14.3. Transport hazard class(es)				
8 (3)	8 (3)	8 (3)	8 (3)	8 (3)
14.4. Packing group				
II	II	II	II	II
14.5. Environmental hazards				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available				

14.6. Special precautions for user

Overland transport


Classification code (ADR)	: CF1
Special provisions (ADR)	: 163, 367
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001, IBC02
Mixed packing provisions (ADR)	: MP15

RAPTOR EPOXY PRIMER HARDENER

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Portable tank and bulk container instructions (ADR) : T7
Portable tank and bulk container special provisions (ADR) : TP2, TP8, TP28
Tank code (ADR) : L4BN
Vehicle for tank carriage : FL
Transport category (ADR) : 2
Special provisions for carriage - Operation (ADR) : S2
Hazard identification number (Kemler No.) : 83
Orange plates :



Tunnel restriction code (ADR) : D/E
EAC code : •3W
APP code : A(fl)

Transport by sea

Special provisions (IMDG) : 163, 367
Packing instructions (IMDG) : P001
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T7
Tank special provisions (IMDG) : TP2, TP8, TP28
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-C
Stowage category (IMDG) : B
Stowage and handling (IMDG) : SW2
Properties and observations (IMDG) : Miscibility with water depends upon the composition. Corrosive contents cause burns to skin, eyes and mucous membranes.

Air transport

PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y840
PCA limited quantity max net quantity (IATA) : 0.5L
PCA packing instructions (IATA) : 851
PCA max net quantity (IATA) : 1L
CAO packing instructions (IATA) : 855
CAO max net quantity (IATA) : 30L
Special provisions (IATA) : A72, A192
ERG code (IATA) : 8F

Inland waterway transport

Classification code (ADN) : CF1
Special provisions (ADN) : 163, 367
Limited quantities (ADN) : 1 L
Excepted quantities (ADN) : E2
Equipment required (ADN) : PP, EP, EX, A
Ventilation (ADN) : VE01
Number of blue cones/lights (ADN) : 1

Rail transport

Classification code (RID) : CF1
Special provisions (RID) : 163, 367
Limited quantities (RID) : 1L
Excepted quantities (RID) : E2
Packing instructions (RID) : P001, IBC02
Mixed packing provisions (RID) : MP15
Portable tank and bulk container instructions (RID) : T7
Portable tank and bulk container special provisions (RID) : TP2, TP8, TP28
Tank codes for RID tanks (RID) : L4BN
Transport category (RID) : 2

RAPTOR EPOXY PRIMER HARDENER

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Colis express (express parcels) (RID) : CE6

Hazard identification number (RID) : 83

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008	1-methoxy-2-propanol - benzyl alcohol
3(a) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	RAPTOR EPOXY PRIMER HARDENER - xylene - 1-methoxy-2-propanol
3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	RAPTOR EPOXY PRIMER HARDENER - xylene - m-phenylenebis(methylamine) - benzyl alcohol
3(c) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	m-phenylenebis(methylamine)
40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	xylene - 1-methoxy-2-propanol

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 651 g/l

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. 3	Flammable liquids, Category 3
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.

RAPTOR EPOXY PRIMER HARDENER

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

SDS EU (REACH Annex II)

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.