

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 SDS Ref. (EU): RLW-SDS Issue date: 3/31/2016 Revision date: 12/3/2020 Supersedes version of: 8/27/2020 Version: 6.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : RAPTOR LINER - WHITE UFI 5JS0-3031-F00D-8FX5 Product code : RLW/1, RLW/200 Product group Coating

Other means of identification Component of: RLW/S4

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

: Industrial use, Professional use Main use category

Use of the substance/mixture : Coatings and paints, thinners, paint removers

Function or use category Coating

1.2.2. Uses advised against

Restrictions on use : Consumer uses: Private households (= general public = consumers)

1.3. Details of the supplier of the safety data sheet

Manufacturer Importer

U-POL Limited U-POL Netherlands B.V. Denington Road Hoorgoorddreef 15

NN8 2QH Wellingborough - United Kingdom 1101BA Amsterdam - Netherlands

T +44 (0) 1933 230310 T +31 20 240 2216

technicalsupport@u-pol.com - www.u-pol.com technicalsupport@u-pol.com - www.u-pol.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: +44 (0) 870 8200418 (24 hrs)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	NHS England, Scotland & Wales	-	Call 111 or a Doctor	In Northern Ireland, contact your local GP or pharmacist during normal hours (www.gpoutofhours.h scni.net)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225 Serious eye damage/eye irritation, Category 2 H319 Skin sensitisation, Category 1 H317 Specific target organ toxicity — Single exposure, Category 3, Narcosis H336 Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412

Full text of H-statements: see section 16

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Adverse physicochemical, human health and environmental effects

Highly flammable liquid and vapour. May cause drowsiness or dizziness. May cause an allergic skin reaction. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS02

GHS

Signal word (CLP) : Danger

Contains : acetone; reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl

1,2,2,6,6-pentamethyl-4-piperidyl sebacate; reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-

tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)

Hazard statements (CLP) : H225 - Highly flammable liquid and vapour.

H317 - May cause an allergic skin reaction.H319 - Causes serious eye irritation.H336 - May cause drowsiness or dizziness.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, open flames, sparks. — No smoking.

P261 - Avoid breathing fume, spray, vapours.

P280 - Wear eye protection, protective clothing, protective gloves.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.

EUH-statements : EUH066 - Repeated exposure may cause skin dryness or cracking.

EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not

breathe spray or mist.

Unknown acute toxicity (CLP) - SDS : 0.58% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation

(Vapours))

2.3. Other hazards

Component		
acetone (67-64-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
2-methoxy-1-methylethyl acetate (108-65-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
n-butyl acetate (123-86-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
acetone substance with a Community workplace exposure limit	(CAS-No.) 67-64-1 (EC-No.) 200-662-2 (EC Index-No.) 606-001-00-8 (REACH-no) 01-2119471330-49	10 – 20	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm]	(CAS-No.) 13463-67-7 (EC-No.) 236-675-5 (EC Index-No.) 022-006-002 (REACH-no) 01-2119489379-17	10 – 20	Carc. 2, H351
2-methoxy-1-methylethyl acetate substance with a Community workplace exposure limit	(CAS-No.) 108-65-6 (EC-No.) 203-603-9 (EC Index-No.) 607-195-00-7 (REACH-no) 01-2119475791-29	3 – 10	Flam. Liq. 3, H226
reaction mass of ethylbenzene, m-xylene and p-xylene	(EC-No.) 905-562-9 (REACH-no) 01-2119555267-33	3 – 10	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
n-butyl acetate substance with a Community workplace exposure limit	(CAS-No.) 123-86-4 (EC-No.) 204-658-1 (EC Index-No.) 607-025-00-1 (REACH-no) 01-2119485493-29	3 – 10	Flam. Liq. 3, H226 STOT SE 3, H336
kieselguhr, soda ash flux calcined	(CAS-No.) 68855-54-9 (EC-No.) 272-489-0 (REACH-no) 01-2119488518-22	< 3	STOT RE 2, H373
phosphoric acid polyester (72243-070628, Germany)		0.3 – 2.5	Eye Irrit. 2, H319
reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	(CAS-No.) 1065336-91-5 (EC-No.) 915-687-0 (REACH-no) 01-2119491304-40	0.3 – 1	Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	(EC-No.) 400-830-7 (EC Index-No.) 607-176-00-3 (REACH-no) 01-0000015075-76	0.1 – 0.25	Skin Sens. 1A, H317 Aquatic Chronic 2, H411

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

First-aid measures after inhalation

First-aid measures after skin contact

That did medadies diter skin contact

First-aid measures after eye contact

First-aid measures after ingestion

: Call a poison center or a doctor if you feel unwell.

: Remove person to fresh air and keep comfortable for breathing.

: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin

irritation or rash occurs: Get medical advice/attention.

: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

: Call a poison center or a doctor if you feel unwell.

12/3/2020 (Revision date) EN (English) 3/26

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : May cause an allergic skin reaction. Repeated exposure may cause skin dryness or

cracking.

Symptoms/effects after eye contact : Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour. Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Safety glasses. Protective clothing. Gloves.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing

vapours, spray, fume. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or

public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

12/3/2020 (Revision date) EN (English) 4/26

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing vapours, spray,

fume. Avoid contact with skin and eyes.

Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash

contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Storage temperature : < 25 °C

Storage area : Store in a well-ventilated place. Special rules on packaging : Keep only in original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

2-methoxy-1-methylethyl acetate (108-65-6)			
EU - Indicative Occupational Exposure Limit (IOEL)			
Local name	2-Methoxy-1-methylethylacetate		
IOEL TWA	275 mg/m³		
IOEL TWA [ppm]	50 ppm		
IOEL STEL	550 mg/m³		
IOEL STEL [ppm]	100 ppm		
Notes	Skin Skin		
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC COMMISSION DIRECTIVE 2000/39/EC		
Ireland - Occupational Exposure Limits	Ireland - Occupational Exposure Limits		
Local name	2-Methoxy-1-methylethylacetate		
OEL TWA [1]	275 mg/m³		
OEL TWA [2]	50 ppm		
OEL STEL	550 mg/m³		
OEL STEL [ppm]	100 ppm		
Notes (IE)	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)		
Regulatory reference	Chemical Agents Code of Practice 2020		

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2-methoxy-1-methylethyl acetate (108-65-6)	
United Kingdom - Occupational Exposure Limits	
Local name	1-Methoxypropyl acetate
WEL TWA (OEL TWA) [1]	274 mg/m³
WEL TWA (OEL TWA) [2]	50 ppm
WEL STEL (OEL STEL)	548 mg/m³
WEL STEL (OEL STEL) [ppm]	100 ppm
Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

acetone (67-64-1)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Acetone	
IOEL TWA	1210 mg/m³	
IOEL TWA [ppm]	500 ppm	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC COMMISSION DIRECTIVE 2000/39/EC	
Ireland - Occupational Exposure Limits		
Local name	Acetone	
OEL TWA [1]	1210 mg/m³	
OEL TWA [2]	500 ppm	
Notes (IE)	IOELV (Indicative Occupational Exposure Limit Values)	
Regulatory reference	Chemical Agents Code of Practice 2020	
Ireland - Biological limit values		
Local name	Acetone	
BLV	50 mg/l Parameter: acetone - Medium: urine - Sampling time: End of shift - Notations: Ns (Non-specific)	
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)	
United Kingdom - Occupational Exposure Limits		
Local name	Acetone	
WEL TWA (OEL TWA) [1]	1210 mg/m³	
WEL TWA (OEL TWA) [2]	500 ppm	
WEL STEL (OEL STEL)	3620 mg/m³	
WEL STEL (OEL STEL) [ppm]	1500 ppm	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)		
Ireland - Occupational Exposure Limits		
Local name	Titanium dioxide	
OEL TWA [1]	10 mg/m³ total inhalable dust 4 mg/m³ respirable dust	
Regulatory reference	Chemical Agents Code of Practice 2020	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)		
United Kingdom - Occupational Exposure Limits		
Local name	Titanium dioxide	
WEL TWA (OEL TWA) [1]	10 mg/m³ 4 mg/m³	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	

kieselguhr, soda ash flux calcined (68855-54-9)		
Ireland - Occupational Exposure Limits		
Local name	Diatomaceous earth, natural, respirable dust	
OEL TWA [1]	1.2 mg/m³	
Regulatory reference	Chemical Agents Code of Practice 2020	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	1.2 mg/m³	

n-butyl acetate (123-86-4)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	n-Butyl acetate	
IOEL TWA	241 mg/m³	
IOEL TWA [ppm]	50 ppm	
IOEL STEL	723 mg/m³ 723 mg/m³	
IOEL STEL [ppm]	150 ppm 150 ppm	
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831 COMMISSION DIRECTIVE (EU) 2019/1831	
Ireland - Occupational Exposure Limits		
Local name	Butyl acetate	
OEL TWA [1]	710 mg/m³	
OEL TWA [2]	150 ppm	
OEL STEL	950 mg/m³	
OEL STEL [ppm]	200 ppm	
Regulatory reference	Chemical Agents Code of Practice 2020	
United Kingdom - Occupational Exposure Limits		
Local name	Butyl acetate	
WEL TWA (OEL TWA) [1]	724 mg/m³	
WEL TWA (OEL TWA) [2]	150 ppm	
WEL STEL (OEL STEL)	966 mg/m³	
WEL STEL (OEL STEL) [ppm]	200 ppm	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	

8.1.2. Recommended monitoring procedures

No additional information available

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

2-methoxy-1-methylethyl acetate (108-65-6)			
DNEL/DMEL (Workers)			
Acute - local effects, inhalation	550 mg/m³		
Long-term - systemic effects, dermal	796 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	275 mg/m³		
DNEL/DMEL (General population)			
Long-term - systemic effects,oral	36 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	33 mg/m³		
Long-term - systemic effects, dermal	320 mg/kg bodyweight/day		
Long-term - local effects, inhalation	33 mg/m³		
PNEC (Water)	PNEC (Water)		
PNEC aqua (freshwater)	0.635 mg/l		
PNEC aqua (marine water)	0.0635 mg/l		
PNEC aqua (intermittent, freshwater)	6.35 mg/l		
PNEC (Sediment)	PNEC (Sediment)		
PNEC sediment (freshwater)	3.29 mg/kg dwt		
PNEC sediment (marine water)	0.329 mg/kg dwt		
PNEC (Soil)			
PNEC soil	0.29 mg/kg dwt		
PNEC (STP)			
PNEC sewage treatment plant	100 mg/l		

acetone (67-64-1)		
DNEL/DMEL (Workers)		
Acute - local effects, inhalation	2420 mg/m³	
Long-term - systemic effects, dermal	186 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	1210 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	62 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	200 mg/m³	
Long-term - systemic effects, dermal	62 mg/kg bodyweight/day	
PNEC (Water)		
PNEC aqua (freshwater)	10.6 mg/l	
PNEC aqua (marine water)	1.06 mg/l	
PNEC aqua (intermittent, freshwater)	21 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	30.4 mg/kg dwt	
PNEC sediment (marine water)	3.04 mg/kg dwt	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

PNEC (Soil)	
PNEC soil	29.5 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	100 mg/l

n-butyl acetate (123-86-4)	
DNEL/DMEL (Workers)	
Acute - systemic effects, dermal	11 mg/kg bw/day
Acute - systemic effects, inhalation	600 mg/m³
Acute - local effects, inhalation	600 mg/m³
Long-term - systemic effects, dermal	11 mg/kg bw/day
Long-term - systemic effects, inhalation	300 mg/m³
Long-term - local effects, inhalation	300 mg/m³
DNEL/DMEL (General population)	
Acute - systemic effects, dermal	6 mg/kg bw/day
Acute - systemic effects, inhalation	300 mg/m³
Acute - systemic effects, oral	2 mg/kg bw/day
Acute - local effects, inhalation	300 mg/m³
Long-term - systemic effects,oral	2 mg/kg bw/day
Long-term - systemic effects, inhalation	35.7 mg/m³
Long-term - systemic effects, dermal	6 mg/kg bw/day
Long-term - local effects, inhalation	35.7 mg/m³
PNEC (Water)	
PNEC aqua (freshwater)	0.18 mg/l
PNEC aqua (marine water)	0.018 mg/l
PNEC aqua (intermittent, freshwater)	0.36 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0.981 mg/kg dwt
PNEC sediment (marine water)	0.0981 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.0903 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	35.6 mg/l

reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)

DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	0.05 mg/kg bw/day
Long-term - systemic effects, inhalation	0.35 mg/m³
DNEL/DMEL (General population)	
Long-term - systemic effects,oral	0.025 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Long-term - systemic effects, inhalation	0.085 mg/m³
Long-term - systemic effects, dermal	0.25 mg/kg bw/day
PNEC (Water)	
PNEC aqua (freshwater)	0.0023 mg/l
PNEC aqua (marine water)	0.00023 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	3.37 mg/kg dwt
PNEC sediment (marine water)	0.337 mg/kg dwt
PNEC (Soil)	
PNEC soil	2 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	10 mg/l

reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5) DNEL/DMEL (Workers)	

reaction mass of ethylbenzene, m-xylene and p-xylene		
DNEL/DMEL (Workers)		
Acute - systemic effects, inhalation	289 mg/m³	
Acute - local effects, inhalation	289 mg/m³	
Long-term - systemic effects, dermal	180 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	77 mg/m³	
DNEL/DMEL (General population)		
Acute - systemic effects, inhalation	174 mg/m³	
Acute - local effects, inhalation	174 mg/m³	
Long-term - systemic effects,oral	1.6 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	14.8 mg/m³	
Long-term - systemic effects, dermal	108 mg/kg bodyweight/day	
PNEC (Water)		
PNEC aqua (freshwater)	0.327 mg/l	
PNEC aqua (marine water)	0.327 mg/l	
PNEC aqua (intermittent, freshwater)	0.327 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	12.46 mg/kg dwt	
PNEC sediment (marine water)	12.46 mg/kg dwt	
PNEC (Soil)		
PNEC soil	2.31 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	6.58 mg/l	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves. Protective clothing. Safety glasses.

Personal protective equipment symbol(s):







8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

Other skin protection

Materials for protective clothing:

Impermeable clothing

8.2.2.3. Respiratory protection

Respiratory protection:

Air-fed respiratory protective equipment should be worn when this product is sprayed

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Colour : white.

Appearance : Viscous. Liquid.
Odour : aromatic.
Odour threshold : Not available
Melting point : Not available

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Freezing point : Not available Boiling point : > 35 °C Flammability : Not applicable **Explosive limits** Not available Lower explosive limit (LEL) Not available Upper explosive limit (UEL) Not available Flash point < 0 °C Auto-ignition temperature Not available Decomposition temperature : Not available рΗ : Not available : 6837.607 mm²/s Viscosity, kinematic

Viscosity, dynamic : 8000 (7000 – 9000) cP (20°C)

Solubility : insoluble in water. Soluble in aromatic hydrocarbons.

Partition coefficient n-octanol/water (Log Kow) : Not available Vapour pressure : Not available Vapour pressure at 50 °C : Not available

Density : 1.17 (1.15 – 1.19) g/cm³

Relative density : Not available Relative vapour density at 20 °C : Not available : Not applicable Particle size : Not applicable Particle size distribution Particle shape : Not applicable Particle aspect ratio : Not applicable Particle aggregation state : Not applicable Particle agglomeration state : Not applicable Particle specific surface area : Not applicable Particle dustiness : Not applicable

9.2. Other information

VOC content : 423 g/l

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : 423 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

2-methoxy-1-methylethyl acetate (108-65-6)	
LD50 oral rat	6190 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	> 5000 mg/kg bodyweight (Equivalent or similar to OECD 402, Rabbit, Male / female, Experimental value, Dermal)
LC50 Inhalation - Rat [ppm]	1728 ppm/4h (4 h, OECD Guideline 403 (Acute Inhalation Toxicity), rat, male/female, Inhalation, vapours)

acetone (67-64-1)	
LD50 oral rat	5800 mg/kg bodyweight Animal: rat, Animal sex: female
LD50 dermal rabbit	20000 mg/kg (Equivalent or similar to OECD 402, Rabbit, Male, Experimental value, Dermal)
LC50 Inhalation - Rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4

libutyltin dilaurate (77-58-7)	
LD50 oral rat	2071 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1207 - 5106
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))

phosphoric acid %, orthophosphoric acid % (7664-38-2)	
LD50 oral rat	301 mg/kg (OECD 423)
LD50 dermal rabbit	2750 mg/kg

solvent naphtha (petroleum), light aromatic (6	4742-95-6)
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 3160 mg/kg (OECD Test Guideline 402)
LC50 Inhalation - Rat (Vapours)	> 6.193 mg/l/4h (4 h, OECD Test Guideline 403, vapours)

	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	
LD50 oral rat		> 5000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity)
	LC50 Inhalation - Rat	> 6.82 mg/l (Other, 4 h, Rat, Male, Experimental value, Inhalation (dust), 14 day(s))

kieselguhr, soda ash flux calcined (68855-54-9)	
	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 401 (Acute Oral Toxicity)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

LC50 Inhalation - Rat	> 2.6 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
LC50 Inhalation - Rat (Dust/Mist)	> 2.6 mg/l/4h (4 h, OECD Guideline 403 (Acute Inhalation Toxicity), rat, male/female, Experimental value)

n-butyl acetate (123-86-4)	
LD50 oral rat	10760 – 12789 mg/kg bodyweight (Equivalent or similar to OECD 423, Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	14112 mg/kg bodyweight (Equivalent or similar to OECD 402, Rabbit, Male / female, Experimental value, Dermal)
LC50 Inhalation - Rat [ppm]	390 ppm/4h
LC50 Inhalation - Rat (Vapours)	> 21 mg/l/4h (4 h, OECD Test Guideline 403, rat, vapours)

reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)LD50 oral rat> 5000 mg/kg (OECD Guideline No. 401 (equivalent to Annex V), limit test, rat, male/female)LD50 dermal rat> 2000 mg/kg (OECD Guideline No. 402 (equivalent to Annex V), limit test, rat, male/female)LC50 Inhalation - Rat5800 mg/l (OECD Guideline 403, 14d, rat)

reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)	
LD50 oral rat	3230 mg/kg (OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), rat, male/female)
LD50 dermal rat	> 3170 mg/kg (OECD Guideline 402 (Acute Dermal Toxicity), read-across,

lithium chloride (7447-41-8)	
LD50 oral rat	526 mg/kg bodyweight Animal: rat, Animal sex: male
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal)), Guideline: EPA OPP 81-2 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 5.57 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)

reaction mass of ethylbenzene, m-xylene and p-xylene	
LD50 oral rat	3523 mg/kg (EU Method B.1 (Acute Toxicity (Oral), rat, male)
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male
LC50 Inhalation - Rat [ppm]	6350 ppm/4h (4 h, EU Method B.2 (Acute Toxicity (Inhalation)), rat, male, Inhalation, vapours)

quartz (14808-60-7)	
LD50 oral rat	> 500 mg/kg

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

calcium carbonate (471-34-1)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method), Guideline: EU Method B.1 bis (Acute Oral Toxicity - Fixed Dose Procedure)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
LC50 Inhalation - Rat	> 3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)
LC50 Inhalation - Rat (Dust/Mist)	> 3 mg/l/4h (4 h, OECD Guidelines 403 (Acute Toxicity Inhalation), rat, male/female, Experimental value)

octamethylcyclotetrasiloxane (556-67-2)	
LD50 oral rat	> 4800 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 2400 mg/kg bodyweight (Equivalent or similar to OECD 402, Rat, Male / female, Experimental value, Dermal)
LC50 Inhalation - Rat	36 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

decamethylcyclopentasiloxane (541-02-6)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	8.67 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EPA OTS 798.1150 (Acute inhalation toxicity), 95% CL: 7,3 - 10,32

Dodecamethylcyclohexasiloxane (540-97-6)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

carbon black (1333-86-4)	
LD50 oral rat	> 8000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
	> 4.6 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Experimental value, Inhalation (dust))

Unknown acute toxicity (CLP) - SDS : 0.58% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation

(Vapours))

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified Carcinogenicity : Not classified.

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7) IARC group 2B - Possibly carcinogenic to humans

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

reaction mass of ethylbenzene, m-xylene and p-xylene		
IARC group	2B - Possibly carcinogenic to humans	
Reproductive toxicity : Not classified		
acetone (67-64-1)		
LOAEL (animal/female, F0/P)	11298 mg/kg bodyweight Animal: mouse, Animal sex: female	
NOAEL (animal/male, F0/P)	900 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: other:Generation not specified (migrated information)	
dibutyltin dilaurate (77-58-7)		
NOAEL (animal/male, F0/P)	1.9 – 2.3 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)	
NOAEL (animal/female, F0/P)	1.7 – 2.4 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)	
phosphoric acid %, orthophosphoric acid	% (7664-38-2)	
NOAEL (animal/male, F0/P)	> 500	
STOT-single exposure :	May cause drowsiness or dizziness.	
acetone (67-64-1)		
STOT-single exposure	May cause drowsiness or dizziness.	
dibutyltin dilaurate (77-58-7)		
STOT-single exposure	Causes damage to organs (thymus).	
solvent naphtha (petroleum), light aromatic (64742-95-6)		
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.	
n-butyl acetate (123-86-4)		
STOT-single exposure	May cause drowsiness or dizziness.	
reaction mass of ethylbenzene, m-xylene and	n-xylene	
STOT-single exposure	May cause respiratory irritation.	
2-methoxypropyl acetate (70657-70-4)		
STOT-single exposure	May cause respiratory irritation.	
STOT-repeated exposure : Not classified		
2-methoxy-1-methylethyl acetate (108-65-6)		
NOAEL (oral, rat, 90 days)	≥ 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)	
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

according to Regulation (EC) No. 1907/2006 (REACH) with it	s amendment regulation (LO) 2013/030	
dibutyltin dilaurate (77-58-7)		
STOT-repeated exposure	Causes damage to organs (thymus) through prolonged or repeated exposure.	
phosphoric acid %, orthophosphoric acid % (7664-38-2)		
NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)	
kieselguhr, soda ash flux calcined (68855-5	4-9)	
NOAEL (oral, rat, 90 days)	3737.9 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure (inhalation).	
reaction mass of ethylbenzene, m-xylene ar	nd p-xylene	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)	
NOAEL (oral, rat, 90 days)	150 mg/kg bodyweight/day (OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), female)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.	
calcium carbonate (471-34-1)		
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)	
decamethylcyclopentasiloxane (541-02-6)		
NOAEL (oral, rat, 90 days)	≥ 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)	
NOAEL (dermal, rat/rabbit, 90 days)	≥ 1600 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)	
Dodecamethylcyclohexasiloxane (540-97-6)		
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)	
Aspiration hazard : Not classified		
RAPTOR LINER - WHITE		
Viscosity, kinematic	6837.607 mm²/s	

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

12/3/2020 (Revision date) EN (English) 17/26

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hazardous to the aquatic environment, short-term

(acute)

: Not classified

Hazardous to the aquatic environment, long-term

: Harmful to aquatic life with long lasting effects.

(chronic)

2-methoxy-1-methylethyl acetate (108-65-6)		
LC50 - Fish [1]	> 100 mg/l Test organisms (species): Oryzias latipes	
EC50 - Crustacea [1]	> 500 mg/l Test organisms (species): Daphnia magna	
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
EC50 96h - Algae [1]	> 1000 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)	
NOEC (chronic)	≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
NOEC chronic fish	47.5 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'	

acetone (67-64-1)	
LC50 - Fish [1]	5540 mg/l (EU Method C.1, 96 h, Salmo gairdneri, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 96h - Algae [1]	> 7000 mg/l (Selenastrum capricornutum, Static system, Fresh water, Experimental value, Nominal concentration)
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)	
LC50 - Fish [1]	155 mg/l Test organisms (species): other:Japanese Medaka
EC50 - Crustacea [1]	19.3 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	27.8 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	61 mg/l (EPA 600/9-78-018, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)
NOEC (chronic)	≥ 2.92 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

n-butyl acetate (123-86-4)	
LC50 - Fish [1]	18 mg/l Test organisms (species): Pimephales promelas
LC50 - Fish [2]	62 mg/l (Leuciscus idus, static system)
EC50 - Crustacea [1]	44 mg/l Test organisms (species): Daphnia sp.
EC50 72h - Algae [1]	674.7 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
NOEC (chronic)	23 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic crustacea	23 mg/l

reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and 3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	
LC50 - Fish [1]	2.8 mg/l (96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value,

Nominal concentration)

12/3/2020 (Revision date)	FN (English)	18/26

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

EC50 - Crustacea [1]	4 mg/l (48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)
ErC50 algae	> 100 mg/l (72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)

reaction mass of ethylbenzene, m-xylene and p-xylene	
LC50 - Fish [1]	2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
EC50 72h - Algae [1]	1.3 mg/l
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'

12.2. Persistence and degradability

2-methoxy-1-methylethyl acetate (108-65-6)	
Persistence and degradability	Readily biodegradable in the soil. Readily biodegradable in water.

acetone (67-64-1)	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.43 g O ₂ /g substance
Chemical oxygen demand (COD)	1.92 g O ₂ /g substance
ThOD	2.2 g O₂/g substance
BOD (% of ThOD)	0.872 (20 day(s), Literature study)

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

kieselguhr, soda ash flux calcined (68855-54-9)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

n-butyl acetate (123-86-4)	
Persistence and degradability	Readily biodegradable in water.
ThOD	2.21 g O₂/g substance
BOD (% of ThOD)	0.46

12.3. Bioaccumulative potential

2-methoxy-1-methylethyl acetate (108-65-6)	
Partition coefficient n-octanol/water (Log Pow)	1.2 (Experimental value, Equivalent or similar to OECD 117, 20 °C)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
(
acetone (67-64-1)	
BCF - Fish [1]	0.69 (Pisces)
BCF - Other aquatic organisms [1]	3 (BCFWIN, Calculated value)
Partition coefficient n-octanol/water (Log Pow)	-0.24 (Test data)
Bioaccumulative potential	Not bioaccumulative.
titanium dioxide; [in powder form containin	g 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)
Bioaccumulative potential	Not bioaccumulative.
kieselguhr, soda ash flux calcined (68855-5	4-9)
Bioaccumulative potential	No test data of component(s) available.
n-butyl acetate (123-86-4)	
BCF - Fish [1]	15.3 (Calculated value)
Partition coefficient n-octanol/water (Log Pow)	2.3 (Test data, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
	yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-droxyphenyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-ene) 2658 – 3430 (502 h, Oncorhynchus mykiss, Flow-through system, Fresh water,
	Experimental value)
Partition coefficient n-octanol/water (Log Pow)	4.6 (Experimental value, Equivalent or similar to OECD 117, 25 °C)
12.4. Mobility in soil	
2-methoxy-1-methylethyl acetate (108-65-6)	
Surface tension	29.4 mN/m (20 °C, 100 vol %, EU Method A.5: Surface tension)
Partition coefficient n-octanol/water (Log Koc)	0.264 (log Koc, QSAR)
Ecology - soil	Highly mobile in soil.
acetone (67-64-1)	
Surface tension	0.0237 N/m
Ecology - soil	No (test)data on mobility of the substance available.

Surface tension	0.0237 N/m
Ecology - soil	No (test)data on mobility of the substance available.

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	
Ecology - soil	Low potential for mobility in soil.

n-butyl acetate (123-86-4)	
Surface tension	0.0163 N/m (20 °C)
Partition coefficient n-octanol/water (Log Koc)	1.268 – 1.844 (log Koc, SRC PCKOCWIN v2.0, QSAR)
Ecology - soil	Low potential for adsorption in soil.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.5. Results of PBT and vPvB assessment

Component	
acetone (67-64-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
2-methoxy-1-methylethyl acetate (108-65-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
n-butyl acetate (123-86-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations.

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

14.1. UN number or ID number

 UN-No. (ADR)
 : UN 1263

 UN-No. (IMDG)
 : UN 1263

 UN-No. (IATA)
 : UN 1263

 UN-No. (ADN)
 : UN 1263

 UN-No. (RID)
 : UN 1263

14.2. UN proper shipping name

Proper Shipping Name (ADR) : PAINT
Proper Shipping Name (IMDG) : PAINT
Proper Shipping Name (IATA) : Paint
Proper Shipping Name (ADN) : PAINT
Proper Shipping Name (RID) : PAINT

Transport document description (ADR)

Transport document description (IMDG)

Transport document description (IATA)

Transport document description (ADN)

Transport document description (ADN)

Transport document description (RID)

UN 1263 PAINT, 3, II

UN 1263 PAINT, 3, II

Transport document description (RID)

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 3

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Danger labels (ADR) : 3

IMDG

Transport hazard class(es) (IMDG) : 3
Danger labels (IMDG) : 3



IATA

Transport hazard class(es) (IATA) : 3
Danger labels (IATA) : 3



ADN

Transport hazard class(es) (ADN) : 3
Danger labels (ADN) : 3



RID

Transport hazard class(es) (RID) : 3
Danger labels (RID) : 3



14.4. Packing group

Packing group (ADR) : II
Packing group (IMDG) : II
Packing group (IATA) : II
Packing group (ADN) : II
Packing group (RID) : II

14.5. Environmental hazards

Dangerous for the environment : No Marine pollutant : No

Other information : No supplementary information available

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1

Special provisions (ADR) : 163, 367, 640D, 650

Limited quantities (ADR) : 5I Excepted quantities (ADR) : E2

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Packing instructions (ADR) : P001, IBC02, R001

Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4

Portable tank and bulk container special provisions : TP1, TP8, TP28

(ADR)

Tank code (ADR) : LGBF
Vehicle for tank carriage : FL
Transport category (ADR) : 2
Special provisions for carriage - Operation (ADR) : S2, S20

Hazard identification number (Kemler No.) : 33
Orange plates :

33 1263

Tunnel restriction code (ADR) : D/E EAC code : •3YE

Transport by sea

Special provisions (IMDG) : 163, 367
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T4

Tank special provisions (IMDG) : TP1, TP8, TP28

EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E
Stowage category (IMDG) : B

Properties and observations (IMDG) : Miscibility with water depends upon the composition.

Air transport

PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 353
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L

Special provisions (IATA) : A3, A72, A192

ERG code (IATA) : 3L

Inland waterway transport

Classification code (ADN) : F1

Special provisions (ADN) : 163, 367, 640D, 650

Limited quantities (ADN) : 5 L

Excepted quantities (ADN) : E2

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01

Number of blue cones/lights (ADN) : 1

Rail transport

Classification code (RID) : F1

Special provisions (RID) : 163, 367, 640D, 650

Limited quantities (RID) : 5L Excepted quantities (RID) : E2

Packing instructions (RID) : P001, IBC02, R001

Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T4

Portable tank and bulk container special provisions : TP1, TP8, TP28

(RID)

Tank codes for RID tanks (RID) : LGBF
Transport category (RID) : 2
Colis express (express parcels) (RID) : CE7

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hazard identification number (RID) : 33

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following res	The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:		
Reference code	Applicable on	Entry title or description	
3(a)	RAPTOR LINER - WHITE; 2-methoxy-1-methylethyl acetate; reaction mass of ethylbenzene, m-xylene and p-xylene; n-butyl acetate; acetone	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	
3(b)	RAPTOR LINER - WHITE ; reaction mass of ethylbenzene, m-xylene and p-xylene ; phosphoric acid polyester (72243-070628, Germany) ; n-butyl acetate ; acetone ; reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylen e) ; reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	
3(c)	RAPTOR LINER - WHITE ; reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene); reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	
40.	RAPTOR LINER - WHITE ; 2-methoxy-1-methylethyl acetate ; reaction mass of ethylbenzene, m-xylene and p-xylene ; n-butyl acetate ; acetone	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	

Contains no substance on the REACH candidate list ≥ 0,1 % / SCL

Contains organic solvents (>= 1%)

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 423 g/l

12/3/2020 (Revision date) EN (English) 24/26

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BLV	Biological limit value
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
EC-No.	European Community number
EN	European Standard
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.